


FICHA TÉCNICA

PIN TORX ROSCA MÉTRICA - CABEZA AVELLANADA



DIMENSIONES (mm)

	DK	K	6mm	8mm	10 mm	12 mm	16 mm	20 mm	25 mm	30 mm	35 mm	40 mm	45 mm	50 mm	55 mm	60 mm	70 mm	80 mm	DRIVER SIZE
M3 x 0.5	5.6	2.0	RTCM 0306	RTCM 0308	RTCM 0310	RTCM 0312	RTCM 0316	RTCM 0320	RTCM 0325										T10
M4 x 0.7	7.8	2.3	RTCM 0406	RTCM 0408	RTCM 0410	RTCM 0412	RTCM 0416	RTCM 0420	RTCM 0425	RTCM 0430		RTCM 0440	RTCM 0445	RTCM 0450			RTCM 0470		T20
M5 x 0.8	9.8	2.8		RTCM 0508	RTCM 0510	RTCM 0512	RTCM 0516	RTCM 0520	RTCM 0525	RTCM 0530		RTCM 0540	RTCM 0545	RTCM 0550		RTCM 0560		RTCM 0580	T25
M6 x 1.0	11.6	3.3		RTCM 0608	RTCM 0610	RTCM 0612	RTCM 0616	RTCM 0620	RTCM 0625	RTCM 0630	RTCM 0635	RTCM 0640		RTCM 0650		RTCM 0660		RTCM 0680	T30
M8 x 1.25	15.8	5.0					RTCM 0816	RTCM 0820	RTCM 0825	RTCM 0830		RTCM 0840		RTCM 0850	RTCM 0855	RTCM 0860		RTCM 0880	T40
M10 x 1.5	19.7	5.1							RTCM 1025		RTCM 1035	RTCM 1040		RTCM 1050		RTCM 1060		RTCM 1080	T45

MATERIAL Y ACABADO

Material: Acero inoxidable A2

Tratamiento de calor: Ninguno

Acabado: Color natural